

300VA Compact, Rugged, Industrial Quality DC/AC Sine Wave Inverter

CSI 280-F3 Series



- Sinusoidal output voltage
- Filtered input
- Conduction/convection cooling
- Compact construction
- Full electronic protection
- Rugged, field-proven design

This rugged DC/AC inverter uses field proven, microprocessor controlled high frequency PWM technology to generate 300VA output power with pure sine wave output voltage. New semiconductor technology and unique design topology simplifies the circuitry and enables a significantly more compact construction, lower weight, lower cost and increased MTBF. The input and output are filtered for low noise. Cooling is via baseplate to a heat-sinking surface and by natural convection. Full electronic protection, generous design headroom and the exclusive use of components with established reliability also contribute to high MTBF. The unit is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

24V, 48V, 110V, 125Vdc $\pm 15\%$ are standard
Consult factory for other inputs

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

Compliant to input and output voltages according to the corresponding standards
Floating output

Standards

Designed to meet
C22.2 No. 107.1 - 01,
UL 458 and EN 60950-1

EMI

EN 55022 Class A
with margins

Output Voltage

115Vac/2.6A continuous at
60Hz or 400Hz; or
230Vac/1.3A continuous at 50Hz
Isolated floating output
Consult factory for other output requirements

Output Wave Form

Sinusoidal

Total Harmonic Distortion

Less than 5% at full load

Line/Load Regulation

Better than $\pm 2\%$ from no load to full load

Load Crest Factor

2 at 90% load

Output Noise

High frequency ripple is better than 500mVrms (20MHz BW)

Output Overload Protection

Current limiting with short circuit protection

Output Overvoltage Protection

Output voltage is limited by internal DC bus voltage

Efficiency

Input voltage dependent
Typically 80% at full load

Operating Temperature Range

0°C to +50°C for full specification
Extended temperature ranges available

Temperature Drift

0.05% per °C over operating temperature range

Cooling

Conduction to customer heat-sink or chassis and natural convection

Environmental Protection

Basic ruggedizing
Full ruggedizing and conformal coating as option

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

140,000 hours at 45°C
Demonstrated MTBF is significantly higher

Indicators

None

Control Input

None
Remote shutdown or enable as an option

Alarm Output

None
Output fail alarm (Form C) as option

Package/Dimensions (W x H x D)

F3: 132 x 64 x 300 mm
(5.2" x 2.5" x 11.8") including mounting flanges and terminals
Mounting holes are clear

Weight

2 kg (4.4 lb)

Connections

12-pole barrier type terminal block with 3/8" spacing
Snap-on cover included

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice.

Terminal Block Pin-out

AC OUTPUT							DC INPUT				
L1	L2	N/A	N/A	N/A	N/A	N/A	GND	-	-	+	+
1	2	3	4	5	6	7	8	9	10	11	12

Please note that ABSOPULSE power supplies are designed and built to customer specifications. The specifications on this data sheet are generic and will vary depending on input/output configuration and other customer requirements. Generic specifications are subject to change

Designer and manufacturer of quality ac-dc power supplies and battery chargers, converters, inverters, dc-output UPS systems, complete rack mount systems and DC-input fluorescent lamp inverters since 1982. Custom or standard. Absopulse is a BABT-approved Facility.



For more information, please see:

September 12, 2013/TS/CL

Made in Canada