



- 10KV Lightning Surge Protection
- Smart Over-Temperature Protection
- Universal AC Input up to 305Vac
- High Efficiency (Up to 90%)
- Active Power Factor Correction
- Constant Current With Dimming Options
- Waterproof up to IP67
- Comprehensive Protection Circuitry
- UL8750 & EN61347 Approvals
- 5 Year Warranty



SELV IP65 IP67 RoHS **CE CB** 

Electrical Specifications

Input

Input Voltage	90-305VAC, 127-431VDC
Input Frequency	47-63 Hz
Input Current	1.6A@115VAC, 0.8A@230VAC, 0.7A@277VAC
Inrush Current	75A Peak @ 230VAC, Cold Start
Power Factor	>0.98 @115VAC >0.95 @ 230VAC
Leakage Current	0.75mA @ 277VAC

General

Efficiency	See table p.5
Isolation	3.75kVAC input to output 2kVAC input to ground 0.5kVAC output to ground
MTBF (MIL-HDBK-217F) Lifetime	220Khrs min. (25°C) >50,000hrs @ 230Vac, 100% load Tcase = 70°C
Dimensions Net Weight	8.23"(209mm)L x 2.48"(63mm)W x 1.57"(40mm)H 2.10 lbs.

Output

Output Voltage	See table p.2
Start Up Delay	<1.5S @ 115VAC, full load <0.5S @ 230VAC, full load
Hold Up Time	>12mS @ 115VAC, full load
Line Regulation	±1%
Output Current Tolerance	±5%
Ripple & Noise	2V pk-pk, measured at 20MHz bandwidth

Environmental

Operating Temp.	-40°C to +70°C (see derating curve p.2)
Operating Humidity	10% to 95% RH, non-condensing
Storage Temperature	-40°C to +85°C
Vibration	IEC 68-2-2-1995/CNS-3629-C6016/GB/T 2423.10-2008; 5-500Hz, 1.0G, 1 Oct/min, 2 cycles: x, y, z, 75 min

Protection

Overvoltage Protection	110-150% of rated output voltage, auto recovery
Over Power Protection	110-150% of rated output power, auto recovery
Short Circuit Protection	No damage to unit, auto recovery
Smart Over-Temperature Protection	When ambient temperature is >70°C±10°C, output load is limited to 75% When ambient temperature is >85±10°C output is disabled. Auto recovery when case temperature is <95°C

Note: All specifications typical at 25°C unless noted.

Safety & EMC

Safety Approvals	UL/cUL 8750 Approved
USA/Canada	EN61347-1, EN61347-2-13
Europe	
EMC Approvals	
EMI	EN55015 (Radiated & Conducted) Class B FCC Part 18 Class B
Harmonic Currents	EN61000-3-2: Class C
Voltage Flicker	EN61000-3-3:
ESD Immunity	EN61000-4-2: 8kV air; 4kV contact
Radiated Immunity	EN61000-4-3: 3V/m
EFT/Burst	EN61000-4-4: ±1.0kV
Surge Immunity	EN61000-4-5: (5kV line-line; 10kV line-ground)
Conducted Immunity	EN61000-4-6: 3Vrms
Magnetic Field	EN61000-4-8: 3 A/m
Dips / Interruptions	EN61000-4-11: 100% reduction for 10ms, 30% reduction for 100ms.

Your Partners in Power..... Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749
 Tel: (978)567-9600 | Fax: (978)567-9601
 Website: www.powerpartners-inc.com

Specifications subject to change.
PDL100U-C-A: 1-JUNE-2015



Distributed by:

Power Sources Unlimited, Inc. Wrentham, MA • Tel: 508-384-1419 • sales@psui.com • www.psui.com





Models and Ratings Chart

Model ¹	Rated Output Current	Current Adjustment Range	Output Voltage	Output Power	Efficiency ²
PDL100U-C1650-A	1650mA	1260-1650mA	31-58V	96W	90%
PDL100U-C1960A	1960mA	1470-1960mA	36-49V	96W	90%
PDL100U-C2290-A	2290mA	1680-2290mA	31-42V	96W	90%
PDL100U-C2740-A	2740mA	2100-2740mA	26-35V	96W	90%
PDL100U-C3560-A	3560mA	2730-3560mA	21-27V	96W	90%

¹Model numbers for IP65 internal potentiometer type dimming shown. For external IP67 rated dimming type, model numbers are PDL100U-CXXXX-D.

²Please reference efficiency vs. Load graph for more precise values.

Derating Curves



Your Partners in Power.....

Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749

Tel: (978)567-9600 | Fax: (978)567-9601

Website: www.powerpartners-inc.com

Specifications subject to change.
PDL100U-C-A: 1-JUNE-2015




Distributed by:


Power Sources Unlimited, Inc. Wrentham, MA • Tel: 508-384-1419 • sales@psui.com • www.psui.com

Mechanical Drawings

Standard Version (Type -A)



Type -D



Your Partners in Power.....

Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749
Tel: (978)567-9600 | Fax: (978)567-9601
Website: www.powerpartners-inc.com

Specifications subject to change.
 PDL100U-C-A: 1-JUNE-2015




Distributed by:
Power Sources Unlimited, Inc. Wrentham, MA • Tel: 508-384-1419 • sales@psui.com • www.psui.com

Dimming Control (-D type only)

For -A type, dimming and output current adjustment is set by internal potentiometer, which can be accessed by removing the "Adj Io" plug on the LED driver case. For -D type, dimming can be controlled in 3 different ways using the Dim(+) and Dim(-) leads: using an external variable/fix resistor, using a 0-10V signal, or by using a PWM signal. If dimming control is not used, leave the Dim(+) and Dim(-) leads floating.

NOTE: Do not connect Dim- to V-, this can damage the LED driver.



External Resistor Dimming

Resistor value	10K Ω	20K Ω	30K Ω	40K Ω	50K Ω	60K Ω	70K Ω	80K Ω	90K Ω	100K Ω	OPEN
% of Rated Output Current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95~105%

0-10V Signal Dimming

Vdc	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN
% of Rated Output Current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95~105%

PWM Signal Dimming

Duty	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN
% of Rated Output Current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	95~105%

Your Partners in Power.....

Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749
Tel: (978)567-9600 | Fax: (978)567-9601
Website: www.powerpartners-inc.com


Specifications subject to change.
PDL100U-C-A: 1-JUNE-2015




Distributed by:

Power Sources Unlimited, Inc. Wrentham, MA • Tel: 508-384-1419 • sales@psui.com • www.psui.com

LED Driver I-V Curve



Efficiency vs. Load



Your Partners in Power.....

Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749
 Tel: (978)567-9600 | Fax: (978)567-9601
 Website: www.powerpartners-inc.com


Specifications subject to change.
 PDL100U-C-A: 1-JUNE-2015



Distributed by:
 Power Sources Unlimited, Inc. Wrentham, MA • Tel: 508-384-1419 • sales@psui.com • www.psui.com



Power Factor vs. Load



Distributed by:

Power Sources Unlimited, Inc. Wrentham, MA • Tel: 508-384-1419 • sales@psui.com • www.psui.com

Your Partners in Power.....

Power Partners, Inc. | 43 Broad Street | Hudson, MA 01749
Tel: (978)567-9600 | Fax: (978)567-9601
Website: www.powerpartners-inc.com

Specifications subject to change.
 PDL100U-C-A: 1-JUNE-2015